

## Grease Spray

Universal lubricating oil

### Technical specifications

**Grease Spray** is a high-adhesion, multi-purpose lubricating grease designed to withstand heavy friction, particularly suitable for lubricating mechanical joints. The product is resistant to water and atmospheric agents; the operating temperature range is from -10°C to +210°C. **Grease Spray** is particularly recommended as a lubricant for industrial assembly chains, plastic molding machines, pins, reducers, guides, extractors, mechanical movements, gears, joints, hinges, drawer slides, locks, hinges, padlocks, high-stress components, reels, drive chains, and moving mechanical parts that require lubrication with a highly adhesive product.

### Instructions for use

Clean the surfaces to be treated before application. Shake the spray can for a few seconds, then spray **Grease Spray** in short bursts from a distance of approximately 15cm. The product is equipped with a special valve and extension tube that allows application even in hard-to-reach areas.

### Application

Apply **Grease Spray** as supplied.

### Consumption

The consumption of **Grease Spray** varies depending on the method of use and the required application.

### Warnings

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on flames or incandescent materials.

Keep away from operating electrical devices.

Use only in well-ventilated areas.

Avoid inhalation and contact with eyes.

Use the product according to good working practices, avoiding dispersion into the environment.

Wear appropriate personal protective equipment (gloves, safety glasses, etc.).

Store indoors in tightly closed original containers, away from weather exposure, frost, and heat sources.

Do not release into the environment: follow local waste disposal regulations.

Always perform a preliminary test before use.

### Packaging

12-pack boxes    400mL    Barcode: 80-20709-000721

### CHEMICAL AND PHYSICAL PROPERTIES

Physical state	Pressurized liquid
Flash Point	Highly flammable
Autoignition temperature	365°C
Packaging format	400mL aerosol can

Technical Data Sheet code: 3001-Revision 01 of 01/10/2025

Via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695  
www.multichimica.it • mailbox@multichimica.it



The information is, to the best of our knowledge, accurate and correct, but any indication and/or suggestion provided is given without guarantee, as the conditions of use are beyond our direct control. In case of uncertainty, preliminary testing is always recommended.