

Olio di Vaseline Spray

Spray lubricant for delicate mechanisms

Technical specifications

Olio di Vaseline Spray is a high-purity oil specifically designed for applications requiring periodic lubrication maintenance. **Olio di Vaseline Spray** is ideal for lubricating delicate mechanisms such as sewing machines, weaving looms, hinges, locks, and office machines. Its special formulation also provides long-lasting protective properties.

Instructions for use

Shake the spray can vigorously before use and spray **Olio di Vaseline Spray** in short bursts from a distance of about 20-30 cm.

Application

Apply **Olio di Vaseline Spray** as supplied.

Consumption

The consumption of **Olio di Vaseline Spray** varies depending on the method of use and the required application.

Warnings

Protect the container from sunlight.

Do not expose to high temperatures or heat sources.

Do not pierce or burn the can.

Use in a well-ventilated area and do not smoke during use.

Use the product following good working practices, avoiding release into the environment.

Wear suitable protective equipment (gloves, safety goggles, etc.).

Store the product indoors in its original, closed packaging, away from weather, frost, and heat sources.

Do not disperse into the environment: follow local regulations for disposal.

Always carry out a preliminary test before use.

Packaging

6-pack boxes 400mL **Barcode: 80-20709-005542**

CHEMICAL AND PHYSICAL PROPERTIES

Physical state	Pressurized liquid
Color	Colorless
Smell	Characteristic
Flash Point	<0°C
Density (T=20°C)	0,75-0,80Kg/L
Packaging format	400mL aerosol can

Technical Data Sheet code: 3017-Revision 01 of 01/10/2025

Via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695
www.multichimica.it • mailbox@multichimica.it



The information is, to the best of our knowledge, accurate and correct, but any indication and/or suggestion provided is given without guarantee, as the conditions of use are beyond our direct control. In case of uncertainty, preliminary testing is always recommended.