

LINDO

Hand cleaning paste

Technical specifications

LINDO is a lemon-scented hand cleaning paste with a high degreasing power. It is an industrial-use product designed to remove stubborn dirt. LINDO is recommended for metalworking industries, printing shops, workshops, carpentries, body shops, and DIY applications.

Instructions for use

Apply a small amount of **LINDO** to dry hands, then rub until the dirt is fully emulsified; rinse thoroughly with plenty of water. Thanks to its high water solubility, the product does not cause sink blockages. For this reason, to maximize its effectiveness, it is recommended to use the product on dry hands.

Application

Apply **LINDO** as supplied.

Consumption

The consumption of **LINDO** varies depending on the method of use and the required application.

Warnings

Product subject to natural shrinkage.

Store in dry, well-ventilated areas at temperatures not below 5°C.

Protect the container from sunlight.

Do not expose to heat sources or direct solar radiation.

Store the product indoors in its original closed packaging, away from weather, frost, and heat sources.

The product is sensitive to frost.

Use the product following good working practices, avoiding environmental release.

Wear appropriate protective equipment (gloves, safety goggles, etc.).

Do not disperse into the environment: follow local regulations for disposal.

Always carry out a preliminary test before use.

Packaging

12-pack boxes 1000mL **Barcode: 80-20709-000288**

4-pack boxes 5000mL **Barcode: 80-20709-000271**

CHEMICAL AND PHYSICAL PROPERTIES

Physical state	Paste
Color	Hazelnut
Smell	Characteristic, lemon
pH	9,5±0,5
Specific weight (T=45°C)	1100±50 g/L

Technical Data Sheet code: 3101-Revision 01 of 01/10/2025

Via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695
www.multichimica.it • mailbox@multichimica.it



The information is, to the best of our knowledge, accurate and correct, but any indication and/or suggestion provided is given without guarantee, as the conditions of use are beyond our direct control. In case of uncertainty, preliminary testing is always recommended.