TECHNICAL DATA SHEET



MARMOSTUCK

Marble filler

Technical specifications

MARMOSTUCK is a product made of unsaturated polyester resins and mineral fillers; it is an excellent filler for correcting cracks or small holes in marble caused by wear or impact. **MARMOSTUCK** is semi-rigid, plastic, and does not sag on vertical surfaces. It is highly resistant to alkalis, diluted acids, and most solvents.

Instructions for use

Thoroughly clean the surface to be treated, ensuring before application that it is dry and free from silicones, waxes, and grease. Mix **MARMOSTUCK** thoroughly with 2-3% paste hardener. Do not use an excessive amount of hardener to avoid peroxide stains during painting.

Application

Apply MARMOSTUCK as supplied, using a spatula.

Consumption

The consumption of MARMOSTUCK varies depending on the method of use and the required application.

Warnings

Do not use the product at temperatures below 5°C.

Store in a cool, dry place.

Use the product following good working practices, avoiding release into the environment.

Wear appropriate protective equipment (gloves, safety glasses, etc.).

Store the product indoors in its original sealed containers, away from weather, frost, and heat sources.

Do not disperse into the environment: follow local regulations for disposal.

Always perform a preliminary test before use.

Shelf life: 12 months from the production date.

Packaging

18-pack boxes 125mL Barcode: 80-20709-000653 12-pack boxes 500mL Barcode: 80-20709-000660

CHEMICAL AND PHYSICAL PROPERTIES

Physical state	Paste
Color	Straw yellow
Smell	Characteristic
Density (T=20°C)	1,75±0,10 Kg/L
Catalysis	100% MARMOSTUCK with 2-3% hardener
Pot life (T=20°C)	5-7 minutes
Drying time (T=20°C)	<30 minutes

Technical Data Sheet code: 3199-Revision 01 of 01/10/2025

