TEGINICAL DATA SILET



GESSO

Indoor masonry plaster

Technical specifications

GESSO is a masonry product for indoor use, ideal for fixing dowels, window frames, door frames, skirting boards, and protective sheaths.

Instructions for use

Pour potable water into a clean container (about 1 volume of water for 2 volumes of powder); add **GESSO** evenly until it surfaces. The substrates to be treated must be solid, compact, rough, free from dust and dirt, and thoroughly dampened. Quickly mix with a spatula or trowel until a homogeneous, pasty consistency is obtained, and use immediately. The material begins to set just a few minutes after mixing, depending on the ambient temperature and the water used. For faster setting time, it is recommended to use lukewarm water. **GESSO** is ready to use: do not mix with other materials. Do not apply stress to the treated items for at least 15 minutes. Clean the tools with water before the final product solidifies.

Application

Apply GESSO as supplied, using a spatula.

Consumption

The consumption of GESSO varies depending on the method of use and the required application.

Warnings

Store in a cool, dry place, in the original intact packaging.

Use the product following good working practices, avoiding environmental dispersion.

Wear appropriate protective equipment (gloves, safety goggles, etc.).

The product is not considered hazardous, but avoid contact with eyes and skin. In case of contact, wash thoroughly with water.

Store the product indoors in its original sealed packaging, away from weather, frost, and heat sources.

Do not disperse into the environment: follow local disposal regulations.

Always perform a preliminary test before use.

Packaging

12-pack boxes 1Kg Barcode: 80-20709-000325 5-pack boxes 5Kg Barcode: 80-20709-002015

CHEMICAL AND PHYSICAL PROPERTIES

Physical state	Powder
Color	White
Smell	Odourless

Technical Data Sheet code: 3201-Revision 01 of 01/10/2025

