TECHNICAL DATA SHEET



STURASVELT

Liquid descaler

Technical specifications

STURASVELT is used in all cases where a drain-opening product is required for pipes. Thanks to its acidic matrix, it can break down various materials such as paper, hair, grease, and anything else that may cause blockages, thereby allowing normal water flow. **STURASVELT** is also recommended for preventive maintenance.

Instructions for use

Pour **STURASVELT** very slowly into the drain after removing any standing water from the fixture. Allow to act for 5-10 minutes, then flush thoroughly with plenty of water.

Application

Apply STURASVELT pure, using a brush, roller, or airless sprayer.

Consumption

The consumption of STURASVELT varies depending on the method of use and the required application.

Warnings

Protect chrome or metal parts: the product's acidic matrix may corrode them.

The product generates intense heat when mixed with water.

Dilute any residues with plenty of water.

Do not add water directly into the bottle.

Do not inhale vapors.

Open with caution.

In case of contact, rinse immediately with plenty of water and seek medical advice if necessary.

The product may damage some steels and aged chrome surfaces.

Do not use simultaneously with other cleaning products or plungers.

Use the product following good working practices, avoiding environmental dispersion.

Wear appropriate protective equipment (gloves, safety goggles, etc.).

Store the product indoors in its original closed packaging, away from weather, frost, and heat sources.

Do not release into the environment: follow local disposal regulations.

Always carry out a preliminary test before use.

Packaging

12-pack boxes 1L (1,85Kg) Barcode: 80-20709-000813

CHEMICAL AND PHYSICAL PROPERTIES

Physical state	Liquid
Color	Blue
Smell	Slightly pungent
Density (T=20°C)	1,80-1,85 Kg/L
pH	<1

Technical Data Sheet code: 3422-Revision 01 of 01/10/2025