

## Stucco Spray Riempitivo

### Filling primer

### Technical specifications

**Stucco Spray Riempitivo** is a high-solid-content product suitable for filling, with good adhesion to many metal substrates, including aluminum and fiberglass. **Stucco Spray Riempitivo** is ideal for repairing and maintaining surfaces subject to wear or scratching, to level and fill small defects such as holes, streaks, scratches, small dents and, in general, imperfections present on the part.

### Instructions for use

Clean the surfaces to be treated before application. Shake the spray can vigorously before use and spray **Stucco Spray Riempitivo** in short bursts and multiple layers from a distance of about 25cm. Repeat the application two or three times at intervals of a few minutes. If necessary, before repainting, sand with very fine abrasive paper.

### Application

Apply **Stucco Spray Riempitivo** as supplied.

### Consumption

The consumption of **Stucco Spray Riempitivo** varies depending on the method of use and the required application.

### Warnings

Protect the container from sunlight. Do not expose to high temperatures or heat sources. Do not pierce or burn the can. Use in a well-ventilated area and do not smoke.

Use the product following good working practices, avoiding release into the environment.

Wear appropriate protective equipment (gloves, safety goggles, etc.).

Store the product indoors in its original, closed packaging, away from weather, frost, and heat sources.

Do not disperse into the environment: follow local regulations for disposal.

Always carry out a preliminary test before use.

### Packaging

6-pack boxes      400mL      Barcode: 80-20709-005443

### CHEMICAL AND PHYSICAL PROPERTIES

Physical state	Pressurized liquid
Color	White
Smell	Characteristic, solvent-like
Flash Point	<0°C
Density (T=20°C)	0,75-0,80Kg/L
Pressure (T=20°C)	4,0±0,5Bar
Pressure (T=50°C)	8,0±0,5Bar
Ford cup 4 viscosity (T=20°C)	11,5 seconds
Solid residue in can	22%
Grindometer fineness	0 to 2 microns
Gloss level	15 gloss
Thickness per coat	12 microns
Thickness with 3 coats	35-40 microns
Dust-free drying	10 minutes
Touch dry	20 minutes
Thorough drying	24 hours
COV content	840g/L - max 640g/L
Packaging format	400mL aerosol can

Technical Data Sheet code: 3012-Revision 01 of 01/10/2025

Via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695

[www.multichimica.it](http://www.multichimica.it) • [mailbox@multichimica.it](mailto:mailbox@multichimica.it)



The information is, to the best of our knowledge, accurate and correct, but any indication and/or suggestion provided is given without guarantee, as the conditions of use are beyond our direct control. In case of uncertainty, preliminary testing is always recommended.