TECHNICAL DATA SHEET



JOLLY RAL FLUORESCENTE

Fluorescent spray colors

Technical specifications

JOLLY RAL FLUORESCENTE is an enamel with excellent adhesion, used to provide greater brightness and brilliance to helmets, car bumpers, motorcycles, bicycles, and wherever a fluorescent effect is required.

Instructions for use

Clean the surface to be painted from grease, dust, and rust.

Turn the can upside down and shake vigorously for about one minute.

Spray from a distance of 20-30 cm with slow, steady horizontal movements; after about one minute, spray vertically.

Application

Apply JOLLY RAL FLUORESCENTE as supplied.

Consumption

The consumption of JOLLY RAL FLUORESCENTE varies depending on the method of use and the required application.

Warnings

Pressurized container.

Protect from sunlight and do not expose to temperatures above 50°C.

Do not pierce or burn even after use.

For professional use only.

Use in a well-ventilated area.

Do not smoke during use.

Use the product following good working practices, avoiding environmental dispersion.

Wear appropriate protective equipment (gloves, safety goggles, etc.).

Store the product indoors in its original sealed packaging and away from weather, frost, and heat sources.

Do not release into the environment: follow local disposal regulations.

Always carry out a preliminary test before use.

Packaging

 6-pack boxes, yellow
 400mL
 Barcode: 80-20709-001810

 6-pack boxes, red
 400mL
 Barcode: 80-20709-001827

 6-pack boxes, green
 400mL
 Barcode: 80-20709-001834

CHEMICAL AND PHYSICAL PROPERTIES

Physical state	Pressurized liquid
Color	Yellow, red, green
Smell	Characteristic, solvent-like
Flash Point	−104°C (referring to the propane content)
Density (T=20°C)	0,75-0,80 Kg/L
Water solubility	Insoluble
Pressure (T=20°C)	3,0±0,5 Bar
Pressure (T=50°C)	7,0±0,5 Bar
VOC content	256g (per 400mL can)

Technical Data Sheet code: 4012-Revision 01 of 01/10/2025

DNV //