# TECHNICAL DATA SHEET



# **FONDO ANTIRUGGINE**

Anti-rust spray paint

## **Technical specifications**

**FONDO ANTIRUGGINE** is a paint used to protect materials and equipment exposed to severe corrosion conditions. The product can be overpainted with any synthetic or acrylic enamel.

#### Instructions for use

Clean the surface to be painted from grease, dust, and rust.

Turn the can upside down and shake vigorously for about one minute.

Spray from a distance of 20-30 cm with slow, steady horizontal movements; after about one minute, spray vertically.

#### **Application**

Apply FONDO ANTIRUGGINE as supplied.

#### Consumption

The consumption of **FONDO ANTIRUGGINE** varies depending on the method of use and the required application.

## Warnings

Pressurized container.

Protect from sunlight and do not expose to temperatures above 50°C.

Do not pierce or burn, even after use.

Use and store in a ventilated, cool place.

Do not smoke during use.

Use the product following good work practices, avoiding environmental dispersion.

Wear appropriate protective equipment (gloves, safety glasses, etc.).

Store the product indoors in its original closed packaging, away from weather, frost, and heat sources.

Do not release into the environment; follow local regulations for disposal.

Always perform a preliminary test before use.

### **Packaging**

6-pack boxes, grey 400mL **Barcode: 80-20709-001957**6-pack boxes, white 400mL **Barcode: 80-20709-002794** 

#### **CHEMICAL AND PHYSICAL PROPERTIES**

Physical state	Pressurized liquid
Color	Grey, White
Smell	Characteristic, solvent-like
Flash Point	−104°C (referring to the propane content)
Density (T=20°C)	0,75-0,80 Kg/L
Water solubility	Insoluble
Pressure (T=20°C)	3,0±0,5 Bar
Pressure (T=50°C)	7,0±0,5 Bar
VOC content	256g (per 400mL can)

Technical Data Sheet code: 4329-Revision 01 of 01/10/2025

