TECHNICAL DATA SHEET



CODE	Art. 1600
TRADE NAME	ACETONE
PRODUCT TYPE	SOLVENT

Technical characteristics

It is used as a solvent for fats, oils, waxes, resins, rubbers, plastics, paints, varnishes, rubber based adhesives.

The product is also an excellent degreaser for metal surfaces, wood, marble, laminates, plastics, textiles, and other materials.

Recommended as stain resistant, does not corrode metals and can be used in all areas where it requires a good degreaser. Because of its purity characteristics it is stable and does not deteriorate. Dilute the paint until it reaches the desired fluidity: with an optimal dilution will enhance the gloss of the paint and relaxation.

Use this as a cold when requesting the removal of pollutants by rag, brush or dipping.

Applications

To dilute:

Dilute the paint until it reaches the desired fluidity: with an optimal dilution will enhance the gloss and the distention of the paint.

To clean:

Use this when requesting the cleaning of surfaces, paintbrushes and spray guns dirty not dried.

Important

Always conduct a preliminary test before using. Use according to good working practices, however, dispose of the product or packaging environment.

Safety data

Refer to the Material Safety Data Sheet

Chemical and Physical Property			
Phisical State	Liquid		
Colour	Colourless		
Odour	Characteristic		
Flash point	<21°C		
Relative density	0,79 ± 0,02 g/cm3		
Boiling point	60°C ca.		

QUALITY CONTROL MANAGER	COMMERCIAL MANAGER	VALIDITY FROM
		18.04.2017

via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695 www.multichimica.it • clienti@multichimica.it • lab@multichimica.it





Multichimica S.p.A. non si assume nessuna responsabilità derivante dall'uso del prodotto, che deve consunque essere sempre conforme alle informazioni becniche formite. Multichimica S.p.A. assicura da parte sua che il prodotto è conforme alle specifiche tecniche.