## TECHNICAL DATA SHEET



CODE	Art. 3410
TRADE NAME	FERBLOCK
PRODUCT TYPE	RUST CONVERTER

## **Technical characteristics**

The product, designed for targeted treatment of rusty surfaces, guarantees lasting protection over time and improves paint anchoring. It penetrates the rust and converts it into a compound firmly anchored to the surface. Rusty and partially painted surfaces can be treated, the surface can be painted after twelve hours after the application of the product.

## **Applications**

Clean the surfaces to be treated by grease and any deposit of non-stick rust.

Apply FERBLOCK with a brush, roller or airless gun.

After completion of the reaction (about 12 hours), remove the excess of product by washing the surface with water, drying and, if desired, varnishing.

## **Important**

Avoid contact and inhalation of the product. Use protective gloves. In case of skin contact or eyes wash immediately with plenty of water and consult a physician.

Keep away from sources of heat, flames, and keep the container tightly closed in a cool, dry place. Always perform a preliminary test before using. Use in accordance with good working practices, however, avoid dispersing the product or packaging in the environment.

Chemical and Physical Property		
Physical state	Liquid	
Colour	Brown	
Odour	Characteristic	
Relative density	1,37 kg/l	
Ph	1	
Water solubility	Soluble	
Flash point	> 70°C	

QUALITY CONTROL MANAGER	COMMERCIAL MANAGER	VALIDITY FROM
		05.09.2016

via G. Galilei 39 • 35035 Mestrino (PD) • tel  $+39\,049\,904\,8611$  • fax  $+39\,049\,900\,1695$  www.multichimica.it • clienti@multichimica.it • lab@multichimica.it





Multichimica S.p.A. non si assume nessuna responsabilità derivante dall'uso del prodotto, che deve comunque essere sempre conforme alle informazioni tecniche fornite. Multichimica S.p.A. assicura da parte sua che il prodotto è conforme alle specifiche tecniche.