

Carbolineum

Protective Wood Preservative

Technical specifications

Carbolineum is an oil-based protective treatment with a characteristic and persistent odor, specifically formulated for the protection of wood exposed to atmospheric agents.

Carbolineum provides excellent waterproofing properties to wood, making it especially suitable for outdoor structures such as fences, old or restored woodwork, outdoor timber constructions, and wood exposed to the elements.

This product is intended for external use only.

Instructions for use

Carbolineum is ready to use.

Stir before application.

Carefully clean the surfaces to be treated: they must be dry, uniform, and solid.

Ensure that all dust and loose parts are removed.

The surfaces must be completely dry before application.

Do not apply in adverse weather conditions that may negatively affect the application, spreading, or drying.

Apply evenly, ensuring full absorption.

Application

Apply by brush, spray, or immersion.

It is recommended to carry out preliminary tests on the surface to be treated.

This product is not suitable for indoor use.

Consumption

Theoretical coverage of **Carbolineum** in 5÷6 m²/L.

Always verify the absorption rate of the surface with a preliminary test.

Warnings

Do not apply on hot, damp, or wet substrates as this may negatively affect product performance.

Do not expose to temperatures >+30°C, heat sources, open flames, or other ignition sources.

Store in a cool, dry area in the original closed containers.

The product is stable for up to 12 months in unopened original containers.

Keep away from direct sunlight, heat sources, open flames, and sparks.

For outdoor use only, due to the intense and persistent odor.

Do not inhale vapors.

Avoid direct contact with skin.

Always perform a preliminary test before use.

Use only in well-ventilated areas.

Via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695

www.multichimica.it • mailbox@multichimica.it



Handle in accordance with standard safety and industrial hygiene practices. Prevent release of the material or its packaging into the environment.

Refer to the Material Safety Data Sheet (MSDS) for detailed handling and safety instructions.

Additional information is provided at the end of this document.

Packaging

6-pack boxes	0,750L
4-pack boxes	5L
Buckets	20L

CHEMICAL AND PHYSICAL PROPERTIES

Physical state		Liquid
Colour		Yellow walnut
Smell		Characteristic
Closed-cup Flash Point	ASTM D3828-87	>40°C
Density (T=20°C)	UNI EN ISO 2811-1	0,93±0,03 Kg/L
Water solubility		Insoluble
Surface drying time		12÷24 hours*
Full drying time (in depth)		24÷48 hours*

*Values recorded at T=23°C and 50% relative humidity. Results may vary depending on the amount of product applied and environmental conditions such as temperature, humidity, ventilation, and substrate absorption..

Technical Data Sheet code: 2245-Revision 01 of 01/07/2025

Via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695
www.multichimica.it • mailbox@multichimica.it



The information is, to the best of our knowledge, accurate and correct, but any indication and/or suggestion provided is given without guarantee, as the conditions of use are beyond our direct control. In case of uncertainty, preliminary testing is always recommended.