# TECHNICAL DATA SHEET



# ACRY PRO

Professional Acrylic Thinner for Primers and Matt Basecoats

## **Technical specifications**

**ACRY PRO** is a professional acrylic thinner for primers and matt basecoats, made from highly selected raw materials (acetates and aromatics). Its formulation ensures excellent dilution of acrylic paints, allowing easy flow and smooth application with maximum performance. Thanks to its purity, **ACRY PRO** is a stable product that does not deteriorate over time.

#### Instructions for use

<u>For thinning:</u> dilute the paint product until the desired fluidity is achieved. With optimal dilution, paint flow and gloss are enhanced.

### **Application**

Apply ACRY PRO undiluted. The product can be applied both by airless spray and by brush.

### Consumption

The consumption of ACRY PRO depends on the type of application, the surface to be treated, and the required dilution ratio. Actual yield may vary depending on environmental conditions (temperature, humidity) and application methods.

It is always recommended to carry out preliminary tests before use.

#### Warnings

Always perform a preliminary test before use to verify compatibility with the material to be treated.

Use the product according to good working practices, avoiding dispersion into the environment.

Wear suitable protective equipment (gloves, safety goggles, etc.).

Store the product in well-ventilated areas, away from sources of heat.

Do not release into the environment: follow local regulations for disposal.

#### **Packaging**

12-pack boxes 1L Barcode: 80-20709-006051 4-pack boxes 5L Barcode: 80-20709-006068

#### **Chemical-Physical Properties**

Physical state	Clear liquid
Colour	Colourless
Smell	Characteristic
Boiling range	80-185°C
Flash Point	<23°C
Density (T=20°C)	[0,858±0,010]Kg/L

Technical Data Sheet code: 1127-Revision 01 of 01/10/2025

Via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695



