

ACRY PRO SLOW

Professional Slow Acrylic Thinner for Primers and Matt Basecoat

Technical specifications

ACRY PRO SLOW is a professional acrylic thinner for primers and matt basecoats, made from highly selected raw materials (acetates and aromatics). It is particularly suitable for thinning pastel paints or coatings with medium to slow drying times and is ideal for use at high temperatures. Its formulation ensures excellent dilution of acrylic paints, allowing easy flow and smooth application with maximum performance. Thanks to its high purity, **ACRY PRO SLOW** is a stable product that does not deteriorate over time.

Instructions for use

For thinning: dilute the paint product until the desired fluidity is achieved. With optimal dilution, paint flow and gloss are enhanced.

Application

Apply **ACRY PRO SLOW** undiluted. The product can be applied both by airless spray and by brush.

Consumption

The consumption of **ACRY PRO SLOW** depends on the type of application, the surface being treated, and the required dilution ratio. Actual yield may vary depending on environmental conditions (temperature, humidity) and application methods.

It is always recommended to carry out preliminary tests before use.

Warnings

Always perform a preliminary test before use to verify compatibility with the material to be treated.

Use the product according to good working practices, avoiding dispersion into the environment.

Wear suitable protective equipment (gloves, safety goggles, etc.).

Store the product in well-ventilated areas, away from sources of heat.

Do not release into the environment: follow local regulations for disposal.

Packaging

12-pack boxes 1L **Barcode: 80-20709-006075**

4-pack boxes 5L **Barcode: 80-20709-006082**

Chemical-Physical Properties

Physical state	Clear liquid
Colour	Colourless
Smell	Characteristic
Boiling range	80-185°C
Flash Point	<23°C
Density (T=20°C)	[0,868±0,010]Kg/L

Technical Data Sheet code: 1128-Revision 01 of 01/10/2025

Via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695

www.multichimica.it • mailbox@multichimica.it



The information is, to the best of our knowledge, accurate and correct, but any indication and/or suggestion provided is given without guarantee, as the conditions of use are beyond our direct control. In case of uncertainty, preliminary testing is always recommended.