

Diluyente Sintetico Professional

For Synthetic and Oleosynthetic Enamels

Slow Evaporation Rate

Technical specifications

Diluyente Sintetico Professional is a universal synthetic thinner formulated with highly purified, carefully selected raw materials. It is designed for thinning synthetic and oleosynthetic enamels. Its slow evaporation rate enhances the gloss and flow of the coating. Thanks to its strong solvent power, **Diluyente Sintetico Professional** can also be used to clean spray guns, brushes, and tools soiled with paint. Due to its high purity, the product is stable and does not deteriorate over time.

Instructions for use

For thinning: gradually mix the thinner into the coating until the desired viscosity is reached. Optimal dilution improves gloss and leveling of the paint film.

For cleaning: use the product as supplied to clean surfaces, brushes, and spray guns contaminated with fresh (non-dried) paint.

Application

Diluyente Sintetico Professional can be used diluted (for thinning paints) or pure (for cleaning tools and surfaces), depending on the required application.

Consumption

The consumption of **Diluyente Sintetico Professional** depends on the type of application, the treated surface, and the required dilution. Actual consumption may vary depending on environmental conditions (temperature, humidity) and application method (spray, brush, immersion). Preliminary tests are always recommended before use.

Warnings

Always carry out a preliminary compatibility test before use. Use the product according to good work practices, avoiding release into the environment. Wear appropriate personal protective equipment (gloves, safety goggles, etc.). Store in well-ventilated areas and away from heat sources. Do not disperse into the environment; follow local regulations for disposal.

Packaging

20-pack boxes	1L
4-pack boxes	5L
Buckets	25L

Chemical-Physical Properties

Physical state	Clear liquid
Colour	Colourless
Smell	Characteristic
Boiling range	95-180°C
Flash Point	>23°C
Density (T=20°C)	≈0,883Kg/L
Vapour density	>1 (air=1)
Water solubility	Insoluble

Technical Data Sheet code: 1807-Revision 01 of 01/09/2025

Via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695

www.multichimica.it • mailbox@multichimica.it



The information is, to the best of our knowledge, accurate and correct, but any indication and/or suggestion provided is given without guarantee, as the conditions of use are beyond our direct control. In case of uncertainty, preliminary testing is always recommended.