

EXTRA CAR

Nitro Anti-Fog Thinner

Technical specifications

EXTRA CAR is a nitro anti-fog thinner obtained from a specific blend designed for thinning glossy or matte nitro primers and finishes. **EXTRA CAR** is free from chlorinated solvents.

Instructions for use

For thinning: mix the product with the paint until the desired fluidity is reached. Optimal thinning enhances the paint's brilliance and smooth flow.

For cleaning: use the product undiluted to clean surfaces, brushes, and spray guns contaminated with paint. Do not leave dirty tools or utensils immersed in the solvent for several hours.

Application

Apply **EXTRA CAR** undiluted.

Consumption

The consumption of **EXTRA CAR** depends on the type of application, the treated surface, and the required dilution. Actual yield may vary depending on environmental conditions (temperature, humidity) and application methods. It is always recommended to carry out preliminary tests before use.

Warnings

Always perform a preliminary test before use to verify compatibility with the material to be treated.

Use the product according to good working practices, avoiding dispersion into the environment.

Wear suitable protective equipment (gloves, safety goggles, etc.).

Store the product in well-ventilated areas, away from sources of heat.

Do not release into the environment: follow local regulations for disposal.

Packaging

4-pack boxes	5L	Barcode: 80-20709-005986
Buckets	20L	Barcode: 80-20709-005993
Buckets	25L	Barcode: 80-20709-006006

Chemical-Physical Properties

Physical state	Clear liquid
Colour	Colourless
Smell	Characteristic, aromatic
Boiling range	60-170°C
Flash Point	<21°C
Density (T=20°C)	[0,850±0,015]Kg/L
pH	Neutral

Technical Data Sheet code: 1904-Revision 01 of 01/10/2025

Via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695
www.multichimica.it • mailbox@multichimica.it



The information is, to the best of our knowledge, accurate and correct, but any indication and/or suggestion provided is given without guarantee, as the conditions of use are beyond our direct control. In case of uncertainty, preliminary testing is always recommended.