

Grafisol

Graffiti Remover

Technical specifications

Grafisol is a product made from an innovative formula specifically designed to remove graffiti, murals, paints, encrustations, quartz-based paints, enamels, spray paints, resinous or rubbery residues, and grease deposits.

Grafisol is ready-to-use and easy to apply. It is ideal for cleaning various types of surfaces such as walls, glass, tiles, marble, metal supports, and floors.

Instructions for use

Apply **Grafisol** directly to the surface to be treated; let it act for a few minutes, then remove the residues using a cloth or an abrasive pad.

Application

Apply **Grafisol** undiluted with a brush.

Consumption

The consumption of **Grafisol** depends on the type of application and the surface being treated. Actual consumption may vary depending on environmental conditions (temperature, humidity) and application methods. Preliminary testing is always recommended before use.

Warnings

Always carry out a preliminary compatibility test before use. Use the product according to good work practices, avoiding release into the environment. Wear appropriate personal protective equipment (gloves, safety goggles, etc.). Store in well-ventilated areas and away from heat sources. Do not disperse into the environment; follow local regulations for disposal.

Packaging

6-pack boxes 1L Barcode: 80-20709-000790

Chemical-Physical Properties

Physical state	Clear liquid
Colour	Colourless
Smell	Characteristic, fruity
Boiling range	145-169°C
Flash Point	>43°C
Density (T=20°C)	≈0,960Kg/L
Vapor density	5 (air=1)
Water solubility	Partially soluble

Technical Data Sheet code: 3015-Revision 01 of 01/09/2025

Via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695

www.multichimica.it • mailbox@multichimica.it



The information is, to the best of our knowledge, accurate and correct, but any indication and/or suggestion provided is given without guarantee, as the conditions of use are beyond our direct control. In case of uncertainty, preliminary testing is always recommended.