

Rimuovi Colla

Facilitates the Removal of All Types of Glue

Technical specifications

Rimuovi Colla is a product made from highly selected raw materials, specifically designed for removing residues of neoprene and vinyl adhesives after the removal of old coverings (carpet, linoleum, etc.). **Rimuovi Colla** leaves the surface perfectly intact.

Instructions for use

Apply the product generously to the surface to be treated and allow it to act until the adhesive softens. Remove the residues using a spatula or, for large areas, a stiff-bristled brush.

Application

Apply **Rimuovi Colla** undiluted using a brush.
The product is ready to use - do not dilute.

Consumption

The consumption of **Rimuovi Colla** depends on the type of application, the surface being treated, and the thickness of the adhesive layer. Actual consumption may vary based on environmental conditions (temperature, humidity) and the application method. Preliminary testing is always recommended before use.

Warnings

Always carry out a preliminary test to verify compatibility with the surface to be treated. Use the product following good working practices, avoiding dispersion into the environment. Wear suitable protective equipment (gloves, safety goggles, etc.). Store in well-ventilated areas, away from heat sources. Do not release into the environment: follow local disposal regulations. Shake well before use.

Packaging

6-pack boxes 1L **Barcode: 80-20709-001148**

Chemical-Physical Properties

Physical state	Viscous liquid
Colour	Colourless
Smell	Characteristic
Boiling range	90-120°C
Flash Point	≈103°C
Density (T=20°C)	≈1,05Kg/L
Brookfield Viscosity [S01, 5rpm] (T=20°C)	≈1600cP

Technical Data Sheet code: 3506-Revision 01 of 01/09/2025

Via G. Galilei 39 • 35035 Mestrino (PD) • tel +39 049 904 8611 • fax +39 049 900 1695
www.multichimica.it • mailbox@multichimica.it



The information is, to the best of our knowledge, accurate and correct, but any indication and/or suggestion provided is given without guarantee, as the conditions of use are beyond our direct control. In case of uncertainty, preliminary testing is always recommended.